

# Elma Laser x2, green cross laser for increased visibility

Rugged, IP54 for every environment

EAN 5706445677009 / EL-NR 6398677000

The brand new Elma Laser x2 line- and X laser is equipped with the latest technology, using green laser light, for enhanced visibility. The human eye is about 4 times more responsive to green light, than classic red, increasing the visible range remarkable, both in- and out doors. Elma Laser x2 provides perfect markings even in long range, eliminating the need to draw on the floor, walls and ceilings. This makes the task of installing shelves, paintings, kitchen tables etc. fast, easy and straightforward.

Elma Laser x2 is indicating horizontal, vertical or both, in an angle of nearly 180°, for perfect leveling, even right above the instrument. Fast and easy, and you have both hands free to work. Just place the laser and turn it on, it's as simple as that.

Forget about time consuming, accurate leveling of the instrument. Elma Laser x2 is self leveling, and if the deviation is too big, the laser will indicate by fast blinking, making operating error impossible. Besides horizontal and vertical lines, you are able to make straight lines in sloping angles, useful e.g. for stairways etc. Lock the Elma Laser x2 to deactivate the self leveling mechanism, and set the angle, simply by placing on standard tripod or on the supplied magnetic adapter. When the leveling is locked, the instrument will indicate, by blinking every 3 second, to prevent mistakes. As additional safety against errors, Elma Laser x2 can't be turned off, when the lock is deactivated, securing the pendulum suspension against transport damage.

Elma Laser x2 cross laser is delivered ready to use in nylon bag, including batteries, manual and magnetic adapter.



## Technical data:

|                      |                           |
|----------------------|---------------------------|
| Visual range:        | To 45m depending on light |
| Vertical accuracy:   | ±3mm@10m                  |
| Horizontal accuracy: | ±3mm@10m                  |
| self leveling:       | ≤4°                       |
| self leveling time:  | ≤3s                       |
| Laser:               | Class II 510nm, 40mW      |
| Mount thread:        | ¼ inch                    |
| Battery:             | 4 pcs. AA 1,5V (incl.)    |
| Battery life:        | ≥4t @ 2 lines             |
| Protection class:    | IP54                      |
| Dimensions:          | 95x80x60mm                |
| Weight:              | 240g                      |

## Related products

EAN

EL-NR

Product

